

Más consistente, mejor, más rápida, más fuerte...

Unidad compacta IP66 – Serie LCS 75

Instalación moderna mediante conectores plug & play

Con el conector LCS 75 las conexiones eléctricas modernas de las luminarias IP66 son tres veces más rápidas que la instalación convencional. Esto es debido a que al no ser necesario abrir la luminaria, se garantiza que conservará su protección IP incluso después de la conexión. Este conector también es adecuado para su uso en entornos que contienen amoníaco.



La gama incluye:

- Conectores de 3 y 5 polos con botones de liberación
- Conector de 5 polos sin pulsadores de desbloqueo para agujeros de carcasa M20
- Tapas protectoras para terminales no utilizados con cableado pasante
- Versiones especiales con alivio de tensión integrado
- Herramientas de montaje para OEMs

Las luminarias a prueba de agua e industriales IP66 no se pueden conectar más rápido.

Aquí está la prueba:

The graphic is a comparison of installation times. On the left, a black background features a white luminaire and the text '2:30' in large white font. On the right, a blue background features the text '0:55' in large white font. Below the time, the text 'IP66 Compact Unit' is followed by 'YOUR ADVANTAGES WITH LCS 75 PLUG & PLAY' in bold. Below this, it says '3 times faster' and 'installation per luminaire!'. A paragraph states: 'The guarantee and IP protection remain unrestricted even after installation as the luminaire does not have to be opened.' The 'ADELS contact' logo is in the bottom right corner. The top left corner has the 'ADELS' logo and the text 'LCS 75 Compact Unit IP66 - The modern installation through plug & play'.

Convencional

Con esta serie de Adels-Contact

Conexión fácil, segura y rentable de luminarias industriales y a prueba de agua

Los conectores de iluminación LCS 75 son la solución ideal para la conexión rápida de luminarias estancas hasta IP66. Aquí, toda la luminaria con su tubo en el interior se puede fijar al techo sin necesidad de abrirla. La conexión eléctrica se realiza desde el exterior. **¡De esta forma la luminaria queda perfectamente montada en menos de 1 minuto!**

Las especificaciones de diámetro se refieren a H05VV-F, para otros cables se debe verificar.



LCS 75/ 3

Order No. 526203

terminal block, 3 pole, housing hole diameter: M20, voltage rating: 250 V, current rating: 16.0 A, cross-section rating: 2.5 mm²



LCS 75/ 3-2

Order No. 526232

terminal block, 2 pole, housing hole diameter: M20, voltage rating: 250 V, current rating: 16.0 A, cross-section rating: 2.5 mm²



LCS 75/ 5

Order No. 526205

terminal block, 5 pole, housing hole diameter: M25, voltage rating: 400 V, current rating: 16.0 A, cross-section rating: 2.5 mm²



ABK 75/ 3

Order No. 526204

protective cap, 3 pole, housing hole diameter: M20




ABK 75/ 5

Order No. 526206

protective cap, 5 pole, housing hole diameter: M25

To get more info, please, go to:



SWITCHES

Pushbuttons, Switches, for PCB, Toggle, E-Stops, Piezoelectrics, Vandal-proof, Microswitches



CONNECTION

Circular connectors, IEC sockets and connectors, Flexible cables



ELECTRONICS

Components for Electronic Protection and Measurement, Relays, PCB connectors



JOYSTICKS

Joysticks, Trackballs, Single Axis, HandGrips



KEYBOARDS

Keyboards, Keypads and Panels



INDICATORS

Led Indicators, Lamps



SENSORS

Reed Sensors, Temperature sensors and Limiters, Proximity sensors



MOTION

Motors, Geared Motors, Encoders, Solenoids, Linear Actuators, PMG



AIR MOVING

AC and DC fans, accessories and ventilation groups