












	Momentary	Alternate	Quiet	
2.5N actuation force	1550x 1.5M operations -40/+75°C silver or gold contacts 	1555x 0.5M operations -40/+75°C silver or gold contacts 	15500 1.5M operations -40/+75°C silver contacts 	 Unimec: through-hole double pole 8 contact functions 1.8mm travel
	1540x >10M operations -40/+160°C silver or gold contacts 	1545x 5M operations -40/+160°C silver or gold contacts 	15420 >10M operations -40/+160°C gold contacts 	
	Standard	Standard	illuminated	
3.5N (3 series) actuation force	3CTL6 through-hole -40/+115°C RAS version 	3ETL6 through-hole -40/+115°C 	3ATL6xx through-hole -40/+115°C 	Multimec 3 series: momentary/ single pole >10 milion operations IP 67 1mm travel 3A LED colours: 00 blue 20 green 40 yellow 80 red 3F LED colours: 00 blue 20 green 40 yellow 65 white 80 red 8020 red/green 2040 green/yellow 8040 red/yellow
	3CTH9 through-hole -40/+160°C 	3ETH9 through-hole -40/+160°C 		
	3CSH9 surface mount -40/+160°C 	3ESH9 surface mount -40/+160°C 	3FTL6xx through-hole -40/+115°C 	
2.0N actuation force	5ETH920 through-hole quiet version RAS version 	5GTH920 through-hole quiet version RAS version 	5GTH920xx through-hole quiet version 	Multimec 5 series: momentary/ single pole >10 milion operations IP 67 Temp. range: -40/+160°C 1mm travel LED colours: 01 blue 22 green 42 yellow 61 white 82 red 8222 red/green 2242 green/yellow 8242 red/yellow
	5ESH920 surface mount quiet version 	5GSH920 surface mount quiet version 	5GSH920xx surface mount quiet version 	
3.5N actuation force	5ETH935 through-hole RAS version 	5GTH935 through-hole RAS version 	5GTH935xx through-hole 	
	5ESH935 surface mount 	5GSH935 surface mount 	5GSH935xx through-hole 	
6.5N actuation force	5ETH965 through-hole RAS version 	5GTH965 through-hole RAS version 	5GTH965xx through-hole 	
	5ESH965 surface mount 	5GSH965 surface mount 	5GSH965xx through-hole 	

	Non-illuminated	Non-illuminated & illuminated			illuminated
ROUND	1SS Ø6.5mm h=8.0 - 15.0mm *for 5E 	1JS Ø9.6mm h=10.4mm 	1DS Ø9.6mm h=14.9mm 	1GAS Ø11mm h=12.5mm 	1IS Ø6.5mm h=10.4 - 15.0mm 
	varimec round Ø5.2; 7.8; 11.6mm h=10.4-22.5mm *for 3E 	1US Ø10.6mm h=14.9mm 	1ZCS Ø14.3mm h=11.7mm 	1GCS Ø15mm h=12.5mm 	1LS Ø6.5mm h=12.0mm; 15.0mm 
		1Z Ø29.5mm h=12.2mm 	1ZW Ø29.5mm h=12.3mm 	aquamec Ø10.6mm h from front panel=14.3mm h=24.2-27.2mm *for 3F/4F 	1ES Ø9.6mm h=14.9mm 
		10R Ø30mm h=10.5mm 	10R16HOMS Ø30mm h=10.5mm 	navimec Ø34.25mm h=11.7/12.2mm 	1FS Ø9.6mm h=14.9mm 
SQUARE/RECTANGULAR	1ZA 18.65x10.1mm h=12.2mm 	1PS 12.5x6.5mm h=15.7mm 	1X 7.4x9.4mm h=18.5mm *for 3F/4F 	1QS 12.5x6.5mm h=15.7mm 	1RS 12.5x6.5mm h=15.7mm 
	1M 25.0x10.1mm h=12.2mm 	1A 12.5x10.1mm h=12.2mm 	1TS 10.6x10.6mm h=14.9mm 	1H 12.5x10.1mm h=12.2mm 	1C + 2C/2D 15.1x15.1mm h=12.2mm 
	varimec square 5.2x5.2; 7.8x7.8; 11.6x11.6mm h=10.4-22.5mm *for 3E 	1B + 2C/2D 15.1x15.1mm h=12.2mm 	1KS 14.3x14.3mm h=19.1mm 	2K 17.75x17.75mm 	1KBS 14.3x14.3mm h=20.2mm 
	16300 7.0x12.6mm h=16.9mm 	10Q 22x22mm h=12.5mm 	10Q16HOMS 22x22mm h=12.5mm 		1KCS 14.3x14.3mm h=20.1mm 
	16700 14.9x14.9mm h=14.6mm 				1YS 15x15mm h=12.5mm *for 5E 
OTHER	2SS extender for 5G snap on caps h=5-10mm 	1N Ø9.6/14.9mm h=14.9mm *for 3F/4F 	1VS 10.6x13.25mm h=14.9mm 	1ZB 90° R=17.5mm h=12.2mm 	
	1TW/1UW/1VW sealing for 1TS/1US/1VS 	1WA 6.5x12.5mm h=15.7mm *for 3F/4F 	1WD 8.0x15.2mm h=15.7mm *for 3F/4F 	1WP 6.5x12.5mm h=15.7mm *for 3F/4F 	