































Switch series

Selection guide

	MOMENTARY	ALTERNATE	QUIET	KEY FEATURES
2.5N actuation force	1550x 1.5M operations -40/+75°C silver or gold contacts 	1555x 0.5M operations -40/+75°C silver or gold contacts 	15500 1.5M operations -40/+75°C silver contacts 	unimec: through-hole double pole 8 contact functions 1.8mm travel
	1540x >10M operations -40/+160°C silver or gold contacts 	1545x 5M operations -40/+160°C silver or gold contacts 	15420 >10M operations -40/+160°C gold contacts 	
	STANDARD	STANDARD	ILLUMINATED	KEY FEATURES
3.5N (3 series) actuation force	3CTL6 through-hole -40/+115°C RAS version 	3ETL6 through-hole -40/+115°C 	3FTL6xxRAS through-hole 	Multimec 3 series: momentary/ single pole >10 million operations IP 67 1 mm travel
	3CTH9 through-hole -40/+160°C 	3ETH9 through-hole -40/+160°C 		
	3CSH9 surface mount -40/+160°C 	3ESH9 surface mount -40/+160°C 		
2.0N actuation force	5ETH920 through-hole quiet version RAS version NO or NC/NO 	5GTH920 through-hole quiet version RAS version NO or NC/NO 	5GTH920xx through-hole quiet version 	Multimec 5 series: momentary/ single pole >10 million operations IP 67 – 1mm travel Temp. range: -40/+160°C Function: normally open (NO) or normal closed/normal open (NC/NO) - two options possible in all actuation forces and both 5G and 5E
	5ESH920 surface mount quiet version NO or NC/NO 	5GSH920 surface mount quiet version NO or NC/NO 	5GSH920xx surface mount quiet version 	
3.5N actuation force	5ETH935 through-hole RAS version NO or NC/NO 	5GTH935 through-hole RAS version NO or NC/NO 	5GTH935xx through-hole 	LED colours: 01 blue - 22 green - 42 yellow 61 white - 82 red - 8222 red/ green - 2242 green/yellow 8242 red/yellow RAS: right angle version only available with through-hole (TH) normal closed (NO) switch
	5ESH935 surface mount NO or NC/NO 	5GSH935 surface mount NO or NC/NO 	5GSH935xx surface mount 	
6.5N actuation force	5ETH965 through-hole RAS version NO or NC/NO 	5GTH965 through-hole RAS version NO or NC/NO 	5GTH965xx through-hole 	
	5ESH965 surface mount NO or NC/NO 	5GSH965 surface mount NO or NC/NO 	5GSH965xx surface mount 