




Maxconn™ Universal Serial Bus & Fire Wire Connectors

MUSB Series: Right Angle Termination, Single and Stacked



Features

- Plug and play technology
- Hot pluggable
- Single 4, stacked 8-position connectors
- Consolidates serial ports and parallel ports, keyboard ports, mouse ports, and game ports
- Compatible with asynchronous and isochronous data transfer methods
- Compatible with Windows operating system
- Standard feature in new PC chipsets
- Eliminates the need for terminators
- Type "A" and "B" available

Performance Specifications

Materials and Finish

Shell: Nickel plated brass, 0.3mm thick
 Insert: PTH: PBT, GF, 94V-0 rated,
 SMT: Nylon PA9T GF, 94 V-0
 Contact Material: Phosphor bronze
 Contact Finish: Gold flash over nickel with tin plated terminals

Electrical Characteristics

Contact Current Rating: 1.5 Amp @ 250 Vac minimum
 Contact Resistance: 30 milliohms maximum
 Dielectric Withstanding Voltage: 500 Vac for one minute
 Insulation Resistance: 1000 megohms minimum

Mechanical Characteristics



Insertion Force: 35 N maximum
 Extraction Force: 10 N minimum

Part Number

4 Position, Right Angle, Single Type A

Dimensions

PCB Layout






143777




Part Number

Right Angle, Single, SMT

Dimensions



PCB Layout






143799


Part Number

4 Position, Vertical, PCB Mount

Dimensions



PCB Layout



143780





MUSB Series: Right Angle Termination, Single and Stacked

Part Number

8 Position, Right Angle, Single, Type A

Dimensions

PCB Layout







143779

Part Number

4 Position, Right Angle, Single, Type B


Dimensions

PCB Layout



143778

MIEEE-P1394 SERIES: Fire Wire Connector



Features

- Compatible with TA1394, IEEE, and JEDEC standards
- Hot pluggable
- Fast data 100 Mbps – 1Gbps
- Through hole or surface mount

Performance Specifications

Materials and Finish

Shell: Tin Plated, Copper Alloy
 Insert: PTH: PBT, GF, 94V-0 rated,
 SMT: Nylon PA9T GF, 94 V-0
 Contact Material: Copper Alloy
 Contact Finish: Gold flash over nickel, tin terminals

Electrical Characteristics


Contact Current Rating: 1 Amp maximum
 Contact Resistance: 30 milliohms maximum
 Dielectric Withstanding Voltage: 500 Vac for one minute
 Insulation Resistance: 100 megohms minimum

Mechanical Characteristics


Extraction Force: 9.8 N minimum, 39.2 maximum

Part Number


Single, Right Angle, Upright Dimensions



PCB Layout



RECOMMENDED PANEL CUTOUT





143782


Part Number

Single, Right Angle. SMT
Dimensions

PCB Layout



RECOMMENDED PANEL CUTOUT





143796


Part Number

Single, Right Angle
Dimensions

PCB Layout



RECOMMENDED PANEL CUTOUT





143784


Part Number

Single, Vertical
Dimensions

PCB Layout



RECOMMENDED PANEL CUTOUT



143797

ERNI Elektroapparate GmbH

Seestrasse 9, Postfach
73099 Adelberg, Deutschland
Tel +49 (0)71 66 50-0
Fax +49 (0)71 66 50-282
info@erni.de

Europe

South America

Africa

ERNI Components, Inc.

12701 Kingston Avenue
Chester, VA 23836 USA
Tel +1 (804) 530-5012
Fax +1 (804) 530-5232
info@ernicomponents.com

North America

Canada

Mexico

ERNI Asia Pte. Ltd.

Blk 4008 Ang Mo Kio Avenue 10
#04-01/02 Techplace I
Singapore 569625
Tel (65) 555-5885
Fax (65) 555-5995

Asia

Maxconn is a division of ERNI Components, Inc.

© ERNI Components, Inc. 2002, Printed in U.S.A.

A policy of continuous improvement is followed and the right to alter any published data without notice is reserved.